



## RAVENOL 2-Takt-ÖI NOT SELF MIX

RAVENOL 2-Takt-ÖI NOT SELF MIX is a mineral high quality two-stroke oil for conventional 2-stroke engines without self-mixing. This unblended oil is produced from carefully selected, pure mineral raffinates. It is resistant to oxidation, non-foaming and has excellent viscosity-temperature characteristics.

Due to the low pour point, this oil can be used in low as well as high temperatures and ensures an impeccable lubrication.

### Application Notes

RAVENOL 2-Takt-ÖI NOT SELF MIX is applicable for all conventional two-stroke engines, for which self-mixing is not specified.

### Quality Classifications

#### Specifications

API SA

#### Characteristic

RAVENOL 2-Takt-ÖI NOT SELF MIX offers:

- Excellent viscosity-temperature characteristics
- Good shear stability
- Outstanding oxidation stability
- Good demulsification characteristics

Characteristics	Unit	Data	Audit
Colour		braun	visual
Density at 20°C	kg/m <sup>3</sup>	884	EN ISO 12185
Viscosity at 40°C	mm <sup>2</sup> /s	147,8	DIN 51 562
Viscosity at 100°C	mm <sup>2</sup> /s	15,0	DIN 51 562
Viscosity index VI		102	DIN ISO 2909
Pourpoint	°C	-24	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

11.02.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41