

RAVENOL ATF Fluid

RAVENOL ATF Fluid is a high quality transmission fluid formulated with a blend of refined base oils with special additives and inhibitors to ensure smooth and efficient operation of the transmission.

Application Notes

RAVENOL ATF Fluid is designed for automatic fluid couplings, torque converters, servo steering systems and other hydrostatic and hydrodynamic systems for which an ATF of Type A Suffix A specification is required.

RAVENOL ATF Fluid is not suitable for use where DEXRON ATF Type B, DEXRON ATF Type D or Ford specification M2C-33 E / F / G are explicitly required in the filling instructional

Quality Classifications

Practice and tested in aggregates with filling

Type A Suffix A (TASA), ALLISON C-4, MAN 339 Typ A, MB 236.2, Renk Doromat, Cat. TO-2

Characteristic

RAVENOL ATF Fluid offers:

- Exceptionally good resistance to aging
- A very good viscosity-temperature behavior
- Effective protection against wear
- · Very good oxidation stability and low foaming tendency
- Enhanced protection against corrosion
- An extremely low pour point
- Compatible with all types of sealing materials
- Miscibility and compatibility with all brands of ATF's with Type A Suffix A specification

Characteristics	Unit	Data	Audit
Colour		rot	visual
Density at 20°C	kg/m³	866	EN ISO 12185
Viscosity at 40°C	mm²/s	35,0	DIN 51 562
Viscosity at 100°C	mm²/s	7,2	DIN 51 562
Viscosity index VI		174	DIN ISO 2909
Flash point (COC)	°C	210	DIN ISO 2592
Pourpoint	°C	-42	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

26.01.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163 33819 Werther Tel.: 05203/9719-0 Fax.: 052039719-40 / 41