



## RAVENOL Automatik-Getriebe-Öl Dexron F III

RAVENOL ATF Dexron F III is high performance semi synthetic ATF (Automatic Transmission Fluid).

RAVENOL ATF Dexron F III is designed with high performance base oil with special additives and inhibition to ensure the proper operation of the automatic transmission.

### Application Notes

RAVENOL ATF Dexron F III was developed for use in automatic transmissions with hydraulic steering systems, converters and transmissions.

RAVENOL ATF Dexron F III is especially suitable for use in transmissions with ATF Dexron F III specification.

RAVENOL ATF Dexron F III is not mixable with other ATF brands.

### Quality Classifications

#### **Specifications**

GM DEXRON III F-30140

#### **Approvals**

MB-Approval 236.1, MB-Approval 236.5, MAN 339 Typ V-1, MAN 339 Typ Z-1 (Alt: MAN 339 Typ F), ZF TE-ML 04D, 14A

#### **Practice and tested in aggregates with filling**

ZF TE-ML 05L, 02F, 03D, 17C, Ford MERCON M-940717, Allison C4, Cat-TO-2, Voith, Nissan

### Characteristic

RAVENOL ATF Dexron F III H offers:

- High and stable viscosity index
- Very low flow point
- Excellent oxidation stability
- Extensive protection against wear, corrosion and foaming
- Well tuned friction properties
- Neutral behavior towards sealing materials
- Neutral behavior by inhibition towards non-ferrous metals

Characteristics	Unit	Data	Audit
Colour		rot	visual
Density at 20°C	kg/m³	857	EN ISO 12185
Viscosity at 40°C	mm²/s	35,90	DIN 51562
Viscosity at 100°C	mm²/s	7,96	DIN 51562
Viscosity index VI		204	DIN ISO 2909
Flash point (COC)	°C	227	DIN ISO 2592
Pourpoint	°C	-48	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

16.02.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41