



RAVENOL Bettbahnöl 150

RAVENOL Bettbahnöl 150 is mineral slide way oil CGLP.

RAVENOL Bettbahnöl 150 is characterized by good lubricating and sliding properties as well as high tackiness.

RAVENOL Bettbahnöl 150 is formulated with mineral base oils and contains additives and corrosion inhibitors to prevent rust formation and stains on slide ways and track surfaces.

RAVENOL Bettbahnöl 150 is compatible with most of drilling-, cutting or grinding emulsions. The lubricant film of the slide way oil is not washed off.

Application Notes

RAVENOL Bettbahnöl 150 can be used for all types of lubrication systems such as pressure, circulating or central lubrication. If necessary it can be applied manually. It can also be used for lubricating bearings and gear boxes.

Quality Classifications

RAVENOL Bettbahnöl 150 is tried and tested for aggregates specifying:

Specifications

DIN 51 502: CGLP

Characteristic

RAVENOL Bettbahnöl 150 offers:

- Very good stick-slip characteristics
- High tackiness
- Good corrosion protection, no rust and stain formation
- Resistance to aqueous metalworking fluids
- Good demulsification

Characteristics	Unit	Data	Audit
Colour		brown	visual
Density at 20°C	kg/m ³	881	EN ISO 12185
Viscosity at 40°C	mm ² /s	145,5	DIN 51 562
Viscosity at 100°C	mm ² /s	15,0	DIN 51 562
Viscosity index VI		102	DIN ISO 2909
Flash point (COC)	°C	240	DIN ISO 2592
Pourpoint	°C	-12	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

12.03.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41