

RAVENOL DW-1 Fluid

RAVENOL DW-1 Fluid is a fully synthetic automatic transmission fluid based on PAO with special additives and inhibition for excellent lubricating.

Due to its special formulation the properties of RAVENOL DW-1 Fluid are crucial. We assure an excellent cold stability.

Application Notes

RAVENOL DW-1 Fluid is specially designed for use in the latest automatic transmissions of Honda.

Please note: Follow manufacturer's original equipment number!

Practice and tested in aggregates with filling

Honda 08200-9008, 08200-9009, Honda 08266-99964, 08266-99967

Characteristic

RAVENOL DW-1 Fluid offers:

- Extremely low pour point
- Improved viscosity and coefficient of friction behaviour
- A very good protection against consumption
- Excellent thermal stability
- Improved EP-characteristics
- A good foaming behaviour
- · Neutral behaviour towards sealing materials
- Reliable protection against corrosion

Characteristics	Unit	Data	Audit	
Colour		rot	-	
Density at 20°C	kg/m³	850	DIN 51 757	
Pourpoint	°C	-53	DIN ISO 3016	

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

19 02 2016

Ravensberger Schmierstoffvertrieb GmbH Postfach 1163 33819 Werther

Tel.: 05203/9719-0 Fax.: 052039719-40 / 41