



## RAVENOL MARINEOIL PETROL SAE 25W-40

RAVENOL MARINEOIL PETROL SAE 25W-40 is a modern high additive treated marine engine oil with synthetic additives. It is suitable for inboard and outboard marine gasoline engines. The high additive content guarantees an excellent effect on the detergent, dispersant and anti corrosion characteristics. It is a top quality product with high safety reserves.

### Application Notes

RAVENOL MARINEOIL PETROL SAE 25W-40 is used in boat engines in case the specification SAE 25W-40 is requested.

### Quality Classifications

#### Approvals

NMMA FC-W® FB-80813K

#### Practice and tested in aggregates with filling

Yamaha, Honda, Suzuki, YANMAR, Mercruiser, VOLVO Penta AB, Kohler, Johnson, Mercury, Evinrude

### Characteristic

RAVENOL MARINEOIL PETROL SAE 25W-40 offers :

- suitability for catalysis
- excellent detergent and dispersant characteristics
- very good cold start characteristics
- a high oxidation stability
- an excellent viscosity temperature behaviour
- an excellent corrosion protection
- high safety reserves
- reduction of emissions

Characteristics	Unit	Data	Audit
Colour		blue	visual
Density at 20°C	kg/m <sup>3</sup>	884	EN ISO 12185
Viscosity at 40°C	mm <sup>2</sup> /s	153,5	DIN 51 562
Viscosity at 100°C	mm <sup>2</sup> /s	17,05	DIN 51 562
Viscosity index VI		120	DIN ISO 2909
Flash point (COC)	°C	235	DIN ISO 2592
Pourpoint	°C	-30	DIN ISO 3016
TBN	mg KOH/g	8,0	DIN ISO 3771
Sulphated ash	%wt.	1,03	-

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

10.02.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41