



RAVENOL OTC - Protect C12+ Concentrate

SILICATE - BORATE - NITRITE - FREE

RAVENOL OTC Organic Technology Coolant Concentrate is an eco-friendly 1.2- Ethanediol (monoethylene glycol) based silicate, borate, nitrite and phosphate-free coolant for cooling circuits in combustion engines which provides maintenance-free corrosion and frost protection. This product is formulated based on a proven inhibitor development by combining silicates with the organic additive technology OAT as an extended life coolant.

The quality of an antifreeze is no longer just determined by the antifreeze effect (which automatically exists in an ethylene-glycol based product), but by the rust protection. That is why automakers subject antifreeze to lengthy corrosion and cavitation tests.

RAVENOL OTC Organic Technology Coolant Concentrate protects the cooling system from rust, frost, and in summer, from overheating.

Application Notes

RAVENOL OTC Organic Technology Coolant Concentrate with highly effective frost and rust protection. Usable in cooling systems with all-aluminium engines. Mix according to chart. Please follow manufacturer instructions.

Instructions: Clean cooling system, test leak tightness, flush.

Mix RAVENOL OTC Organic Technology Coolant Concentrate with clean water (per mixing chart) and add. Allow engine and heater to warm up, add coolant to fill level.

MAN information for use: Mixing prohibited with Type NF and Type N. Do not use silicone radiator hoses per MAN 334 Type 3 (blue) with coolants per MAN 324 Type SNF.

Quality Classifications

RAVENOL OTC Organic Technology Coolant Concentrate is tried and tested for aggregates specifying:

Specifications

MB 325.3, VW/AUDI TL 774 D/F (acc. to G 12 Plus quality), OPEL GM 6277 M, OPEL GM B 040 1065, Ford WSS-M 97 B44D (from model year 1999), FORD 1336797, FORD 1336807, FORD 1365305, PORSCHE, Mitsubishi 0103044, 0103045, MZ311986, Toyota 08889-00115, 08889-01005, 08889-80014, 08889-80015, 00272-1LLAC, VOLVO 9437650, 9437651, VW G012A8FM1, G012A8FM8, G012A8GM9

Approvals

MAN 324 SNF, VW TL 774 Ausführung F, DEUTZ DQC CB-14

Characteristic

RAVENOL OTC Organic Technology Coolant Concentrate offers:

- Excellent for aluminium alloy engines
- Good reserve alkalinity
- Premium corrosion additives for optimal rust protection for all metals and metal alloys used in cooling systems, including aluminium
- Prevents sediments and foaming in the cooling system
- Compatible with elastomers used in automotive radiators
- Can be mixed with other coolant types

| Characteristics | Unit | Data | Audit |
|------------------------------|-------------------|---------------|--------------|
| Colour | | violet / lila | visual |
| Density at 20°C | kg/m ³ | 1130 | EN ISO 12185 |
| Flash point | °C | 110 | ASTM D 51758 |
| Boiling point | °C | 175 | ASTM D 1121 |
| pH- Wert | | 7,8 | ASTM D 1287 |
| Reserve alkalinity | ml 0,1 n HCL | 5,5 | ASTM D 1120 |
| Water content | Gew.-% | 5 | ASTM D 1123 |
| Freezing point (50 %-Lösung) | °C | -35 | ASTM D 1177 |

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

10.03.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41