



RAVENOL STOU SAE 15W-30

RAVENOL STOU SAE 15W-30 is a multi-purpose super universal tractor oil for agricultural machinery, excavators and construction equipment made from specially selected solvent-refined base oils. It is formulated to meet the requirements of all major tractor manufacturers as listed below, and can be used in engines, transmissions and hydraulic systems of most equipment in all seasons which require this grade of oil.

Application Notes

RAVENOL STOU SAE 15W-30 has a wide range of applications in engines, transmissions and hydraulic systems of many tractors and is suitable for use as motor oil for both petrol and diesel engines, transmission oil (including wet brakes and PTO transmissions) and as a hydraulic oil where this specification of product is required. Can also be used as compressor oil.

Quality Classifications

Specifications

API CE, API SF, API GL-4, ACEA E1, ACEA E2

Practice and tested in aggregates with filling

SAE 80W, API GL 4, MIL-L-2105, Allison C-4, Caterpillar TO-4, ZF TE-ML 06B, ZF TE-ML 07B, HLP ISO VG 68, Vickers-Pumpentest, Ford-Pumpentest, Denison HF 2, John Deere J 27 A, J20 C/D, Ford NH 024C, Ford NH 324B, Ford NH 540B, Massey-Ferguson M 1127, Massey-Ferguson M 1139, Massey-Ferguson M 1144, Case International J I Case MS 1118/1209/1206, FIAT AF 87, International Harvester B6, Holman Compair/Atlas Copco Kompressor

Characteristic

RAVENOL STOU SAE 15W-30 provides:

- Excellent viscosity-temperature behaviour
- Exceptional cold starting abilities
- Excellent detergent and dispersant properties
- High resistance to ageing

Characteristics	Unit	Data	Audit
Colour		gelbbraun	visual
Density at 20°C	kg/m ³	881	EN ISO 12185
Viscosity at 40°C	mm ² /s	76,6	DIN 51 562
Viscosity at 100°C	mm ² /s	10,5	DIN 51 562
Viscosity index VI		122	DIN ISO 2909
Flash point (COC)	°C	220	DIN ISO 2592
Pourpoint	°C	-35	DIN ISO 3016
TBN	mg KOH/g	10,9	DIN ISO 3771
Sulphated ash	%wt.	1,45	-

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

09.02.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41