



RAVENOL Super Performance Truck SAE 5W-30

RAVENOL Super Performance Truck SAE 5W-30 is a high alloyed USHPD low friction engine oil for commercial vehicles. Because of the use of synthetic basic oils the viscosity area 5W-30 could be realised. Because of the cold viscosity SAE 5W a definite cold start (low cold start corrosion) and a supply of all lubrication areas is guaranteed as quickly as possible at very low outside temperatures. Extreme stress applications are controlled by the high temperature viscosity SAE 30. Minimized friction loss and wear.

Application Notes

RAVENOL Super Performance Truck SAE 5W-30 is a high-performance engine oil for commercial vehicles which can be used the whole year and which is adapted to the new exhaust gas emission rules (also for EURO I, II, III, IV and EURO V engines).

RAVENOL Super Performance Truck SAE 5W-30 is suitable for oil change intervals up to more than 100.000 km according to the manufacturer's specifications.

Quality Classifications

RAVENOL Super Performance Truck SAE 5W-30 is approved, tried and tested for aggregates specifying:

Specifications

API CI-4/CF, ACEA E4/E7

Approvals

MTU Typ 3, MAN M 3277, Volvo VDS 2, Cummins CES 20076, 20077, 20078, Renault RXD, License: API CI-4

Practice and tested in aggregates with filling

MB 228.5, MB 235.28, IVECO, Volvo VDS 3, MACK EO-M Plus, Voith Retarder B, Global DHD-1, JASO DH-1, SCANIA LDF-3

Characteristic

RAVENOL Super Performance Truck SAE 5W-30 offers:

- Protection against corrosion
- An excellent oxidation stability
- An excellent high temperature stabilit
- Excellent detergent and dispersant attributes
- Profitability because of a low fuel consumption
- Long endurance because of a high oxidation stability
- Excellent cold start attributes
- A very good viscosity temperature behaviour
- Low evaporation

| Characteristics | Unit | Data | Audit |
|--------------------|--------------------|--------------|--------------|
| Colour | | yellow-brown | visual |
| Density at 20°C | kg/m ³ | 858 | EN ISO 12185 |
| Viscosity at -30°C | mPa.s | 6000 | DIN 51 377 |
| Viscosity at 40°C | mm ² /s | 75 | DIN 51 562 |
| Viscosity at 100°C | mm ² /s | 12,2 | DIN 51 562 |
| Viscosity index VI | | 162 | DIN ISO 2909 |
| Flash point (COC) | °C | 235 | DIN ISO 2592 |
| Pourpoint | °C | -42 | DIN ISO 3016 |
| TBN | mg KOH/g | 14,8 | DIN ISO 3771 |
| Sulphated ash | %wt. | 2,0 | DIN 51 575 |

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

20.10.2015

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41