



RAVENOL WATERCRAFT 4-Takt

RAVENOL WATERCRAFT 4-Takt is a synthetic 4-stroke engine oil based on high quality Polyalphaolefin base oils together with a specialist additive package designed especially for use in marine petrol engines.

RAVENOL WATERCRAFT 4-Takt The formulation ensures optimum oil change intervals, a high corrosion protection and low oil and fuel consumption.

Application Notes

RAVENOL WATERCRAFT 4-Takt is suitable for use in water-cooled 4-stroke engines operating in both fresh and sea water environments, and especially where a lubricant is required to meet NMMA FC-W standard.

Follow the manufacturer's recommendations.

Quality Classifications

RAVENOL WATERCRAFT 4-Takt is approved, tried and tested for aggregates specifying:

Specifications

API SG, NMMA FC-W

Characteristic

RAVENOL Watercraft 4-Takt offers:

- Excellent corrosion protection in all oil-wetted engine parts
- An adhesive, pressure-and temperature-resistant oil film
- Exceptional anti-wear properties
- High level of detergent and dispersant properties for cleaner engines

| Characteristics | Unit | Data | Audit |
|--------------------|--------------------|-------|--------------|
| Colour | | blue | visual |
| Density at 20°C | kg/m ³ | 872 | EN ISO 12185 |
| Viscosity at 40°C | mm ² /s | 102,4 | DIN 51 562 |
| Viscosity at 100°C | mm ² /s | 14,8 | DIN 51 562 |
| Viscosity index VI | | 156 | DIN ISO 2909 |
| Pourpoint | °C | - 30 | DIN ISO 3016 |
| TBN | mg KOH/g | 7,5 | ISO 3771 |

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

04.12.2015

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41